True Round Fire Damper • 1½ Hr. Rated • Curtain Blade • Dynamic • Horizontal and Vertical Mount • Galvanized Steel

Standard Construction and Materials

FRAME: 20 GA. galvanized steel for dampers ≤ 10" diameter

16 GA. galvanized steel for dampers ≥ 11" diameter

BLADE: Stainless steel curtain type. FUSIBLE LINK: UL-Listed for 165°F, replaceable.

FINISH: Mill

Options

212°F fusible link

Retaining angle rings (sizes 6" - 24") Retaining plate and clip angles Optional 12" deep x 20 GA. sleeve

Notes

- 1. Nominal deductions of 1/4" will be made to the diameter given.
- 2. Dampers available in 1" increments only.
- 3. Dampers approved for static or dynamic applications and are qualified for both horizontal and vertical installations.

UNDERWRITERS LABORATORIES INC.®

CLASSIFICATION OF MODEL

FIRE RESISTANCE RATING 11/2 HOUR



FILE # R6462





This fire damper meets the construction and performance requirements of:

- · Underwriters Laboratories Inc. Standard 555
- National Fire Protection Association Standard 80, 90A, 101
- California State Fire Marshal Listing #3225-0412:002
- · Underwriters Laboratories Inc. Approved for dual direction airflow and dynamic closure for vertical mount and horizontal mount.
- Underwriters Laboratories Inc. Classified for use in fire resistive ratings of less than 3 hours.


Damper Sizes

	3000 fpm, 4 in. w.g.				
Horizontal & Vertical	Horizontal & Vertical				
Minimum Size	Maximum Size				
4" dia.	24" dia.				









Damper Detail with optional 12" deep x 20 GA. sleeve (Blade Closed)

										TA SO
ltem #	Qty	Damper Size	Horizontal	Vertical	165°F	212°F	Optional			000
			Orientation		Fusible Link		Sleeve	'		<u>Union Made</u>
Arch. / Eng.:					EDR:		ECN:		Job:	
Contractor:										
Project:					Date:		DWN:		DWG:	

In the interest of product development, Cesco Products reserves the right to make changes without notice.

Not to scale.



450 Riverside Dr • Wyalusing PA, 18853 Phone: 570-746-1888 • Fax: 570-746-9286 www.cescoproducts.com